

**Conduit Fittings-PVC Coated  
T&B Catalog Number:**

ST1-G

**UPC Number:** 70450843903**Status:** Active**Description:**

1 in. Dark Gray PVC Coated Straight Liquidtight Connector. Fitting material-Steel.

**Features**

A minimum of .040 in. (40 mil) PVC coating is bonded to the exterior.

Double coated with a nominal .002 in. (2 mil) blue urethane on both the interior and exterior, before PVC coating is applied.

Pressure-sealing sleeves are designed to protect the connection.

PVC coated connectors are available in straight, 45 degree and 90 degree configurations

Ocal uses T&B Industrial Liquidtight fittings to insure quality installations.

**Application**

To positively bond conduit to box or enclosure

**General**

Custom_Finish	lt_1_s
Trade Size (inches)	1
Material	Steel
Finish	PVC Coated
Color	Dark Gray

**Dimension Information**

Pipe Size (Metric Size Designator*)	27
Dimension A (inches)	1 7/8
Dimension B (inches)	2 1/16
Dimension C (inches)	3/4

**Technical Information**

Chemical Resistance Chart Available on Website

**Specifications**

Ocal Specification Guide-1995 Master Format-PDF	Available on Website
Ocal Specification Guide-1995 Master Format-DOC	Available on Website
Ocal Specification Guide-2004 Master Format-PDF	Available on Website
Ocal Specification Guide-2004 Master Format-DOC	Available on Website

**Packaging**

Package in Units	20
T&B Sold in UOM	Each
T&B Weight Per UOM	0.5 lbs. Each

**Application Support**

Ocal PVC Coated Conduit System Available on Website

Ocal Specifications	Available on Website
Recommended Installation Procedures	Available on Website
Product Overview-Conduit Outlet Bodies	Available on Website
NEMA Standards-RN 1	Available on Website
NEC 310-16 - Conductors for General Wiring	Available on Website
NEC Table 8	Available on Website
<b>Notes</b>	
	Dimensional values are of uncoated liquidtight fittings.
	Metric size designator (ANSI C80. 1-1994)

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email:[techsupport@tnb.com](mailto:techsupport@tnb.com)